

**DAV MODEL SCHOOL
FRI-828108**

Name of the work: External & Internal finishing and allied work of Model School at FRI Digwadih.

Sealed tender are invited for the above work at DAV Model School, CFRI , Digwadih from eligible civil contractors those who have carried out Civil works in Govt / Semi Govt organization, private etc fulfilling the following requirements.

- 1) All the bidders are requested to submit experience of having successfully completed Three, Two or One similar type of work for an amount equal to 40%, 60%, or 80% of estimated cost respectively during last seven years.
- 2) GST Registration Certificate as applicable.
- 3) Income Tax/ PAN Card.
- 4) Computerized Price bid documents (Rate and Amount)

Tender paper issued to the Contractor:


(Signature of Principal)
DAV MODEL, FRI

(N.B: The sheet is required to submit with price bids in sealed envelope).

(Signature of Contractor)

**DAV MODEL SCHOOL
FRI-828108**

Name of the work: External & Internal finishing and allied work of Model School at FRI Digwadih.

Quoted Price : Rs.

(Rupees -----)

(Signature of Contractor)

(N.B: The sheet is required to submit with price bids in sealed envelope).

Name of Work: External & Internal finishing and allied work at Model DAV School , FRI Digwadih

SI.No	Description of items	Unit	Qty	Rate(in words & figures)	Amount
1	Finishing walls with textured exterior paint of required shade: Old work (Two or more coats on existing cement paint surface applied @ 3.28 ltr/ 10 sqm, including necessary repairs to scratches and sand papering the surface for smoothness.	Sqm	4624		
2	Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade: Old work (one or more coats) including smoothing of old existing surface with putty wherever is required.	Sqm	6320		
3	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: One or more coats on old work.	Sqm	340		
4	15 mm cement plaster with mix (1:6) on the rough side of half brick wall.	Sqm	150		
5	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sqm and including cutting the patch in proper shape and preparing and plastering the surface of the walls complete including disposal of rubbish to the dumping ground within 50 metres lead : with cement mortar 1 : 4 (1 Cement : 4 fine sand).	Sqm	250		
6	6 mm cement plaster : 1 : 3 (1 Cement : 3 Coarse sand)	Sqm	250		
7	Providing and laying in position cement concrete of specified grade including the cost of centring and shuttering all work up to floor V' level 1 : 1.5 : 3 (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size)	Sqm	220		
8	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS : 15622, of approved make, in all colour sand shades, laid on 20 mm thick cement mortar 1:4 (1 cement : 4 coarse sand), including grouting the joints with white cement and matching pigments etc., complete Size of Tile: 600x600 mm.	Sqm	155		
9	Making rough the hard surface/floor by chiseling including removing of the rubis	Sqm	155		
10	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level: Thermo-Mechanically Treated bars	KG	200		
	Sign Of Contractor				Rs.